



Ground warning sign
Ref. 7010-20



Product description

Ground warning signs for marking the location of an emergency exit within the workplace to ensure access is maintained at all times. High quality adhesive suitable for use on all flat, clean surfaces indoor (excluding carpet), and will function perfectly in temperatures ranging from -20°C to +60°C. Semi-matt and antiskid surface certified according to DIN standards 51097 (grade A) and DIN 51130 (grade R9). The non-reflective coating ensures optimum readability. Flexible and resistant adhesive PVC. Positioning advice on reverse of sticker.
Dim. 700 x 350 mm Thickness 0.2 mm, will not damage or peel off if a fork-lift truck is driven over it.

! During the installation of these stickers it is recommended to inform staff of their significance because it is everyone's duty to take care of their security at the workplace.

High quality materials	Complies with all known safety standards	Easy fitting process
<ul style="list-style-type: none"> High performance adhesive for optimum adherence Non-reflective coating for optimum readability even in direct lighting Antiskid Very thin to prevent tripping hazard and damage from the frequent passage of fork lift trucks, etc 	<ul style="list-style-type: none"> ISO 7010 Pictograms complying with standards and perfectly understandable for everyone DIN 51130 R9 DIN 51097 A Antiskid Non-flammable 	<ul style="list-style-type: none"> Half-moon shape for easy fitting Instruction video Economical and simple can be applied in 1 min Dimensions 700x350 Thk.0,2 mm Clean, stain free removal possible

Positioning advice:	
<ul style="list-style-type: none"> Minimum application temperature: + 10°C. Carefully clean the surface where the sticker will be placed: it must be free of dust, degreased and completely dry. Remove the protective film from the adhesive sticker. Apply the sticker in the desired location (taking into account alignment with the area to be highlighted). Press down from the inside of the sticker to the outside (to remove air bubbles). 	<ul style="list-style-type: none"> It is forbidden to walk on the sticker during the first 24 hours of placement, in order that the adhesive sticks perfectly to the surface.
To remove	
<ul style="list-style-type: none"> Heat the sticker to facilitate removal (for example: with a hair dryer) then use a scraper. Carefully clean the surface with a solvent to remove any remaining adhesive residue. 	

Available colours

Ref.	Product Code	UoS Barcode	Inner box Barcode	Outer box Barcode	Pallet Barcode
7010-20	1701020031	3462159009247	3462159009254	NC	3462159009261

Intrastat code

3919908099

Logistics data

Ref.	UoS			Inner Box			Outer Box			Pallet				
	Dimensions mm	Unit weight Kg	Pack Qty	Dimensions mm	Gross weight kg	Unit weight kg	Pack Qty	Dimensions mm	Gross weight kg	Unit weight kg	Pack Qty	Dimensions mm	Gross weight kg	Unit weight kg
7010-20	700 x 350 H 0,2	0,095	10	715 x 360 H 14	1,19	0,95	NC	NC	NC	NC	900	1200 x 800 H 545	117	86



Protect access to emergency exits

The **Regulatory Reform** (Fire Safety) Order 2005 says that the responsible person as well as everyone in the workplace must make sure that:

Routes to emergency exits from premises and the exits themselves are kept clean at all times.
(Article 14)